

Sun Frost RF4 - Refrigerator/Freezer



The Sun Frost RF4, R4, and F4 are Sun Frost's smallest refrigerators and freezers. Like the R10 and F10, they have the same width and depth as the larger units. The RF4 consists of a refrigerator with an ice tray freezer section. For convenience, these units would require a higher base cabinet, or they could be placed on a countertop. The 4 cubic foot models are also ideal for use in bus conversions, boats and RVs.

Sun Frost refrigerators and freezers are so outstandingly energy-efficient, powering a home with solar power or other low output energy sources is both feasible and affordable. All models are available in 12, 24, 48 volt DC, or 110 or 220 volt AC. Even in a home using conventional utility power, energy consumption for refrigeration is typically cut by a factor of five!

Sun Frost participates in the U.S. government ENERGY STAR® program, and several of the models bear the ENERGY STAR label.

In addition to unrivaled energy efficiency, Sun Frost offers amenities not found in conventional refrigerators, such as high humidity, food-saving storage, ultra-quiet operation and an easy-to-clean interior.

Every Sun Frost is custom crafted - you choose the hinge side and finish. Your Sun Frost can be finished with a number of laminate or wood finishes. Sun Frost is now also offering a stainless steel option.

Model	Description	Daily Energy Use (amp hrs @ 12 VDC / kwh @ 110 VAC)		Dimensions (see clearances below)			Shipping (export add 40 lbs.)	
		at 70°F 21°C	at 90°F 32°C	Height	Width	Depth	Weight	Volume
RF4	Refrigerator w/ ice tray	12 amp-hrs .14 kwh	18 amp-hrs .21 kwh	31.5"	34.5"	27.75"	160 lb.	23 C.F

Voltage: All models are available in 12 volt DC, 24 volt DC, 48 volt DC, 110AC, or 220AC. Listed energy consumptions are for 12 volt units and 110AC; 24 volt units use half the listed amp hours. KWHs are listed for AC units. **48 volt DC:** Please call for pricing.

Clearance: The doors are mounted on a continuous stainless steel piano-style hinge. **It is important to allow an additional 3.75" width on the hinge side for the door to open.** All units require minimum 6" clearance above the unit to allow for heat ventilation. Also, PLEASE NOTE: Oak veneers add a quarter of an inch to overall exterior dimensions, all other wood veneers add a half an inch.

Interior Dimensions:

Model	Freezer					Refrigerator					Total Volume	
	Dimensions (inches)			Volume		Dimensions (inches)			Volume		CF	Liters
	Height	Width	Depth	CF	Liters	Height	Width	Depth	CF	Liters		
RF4	2.25	26	20	.68	19.2	10.5	26	20	3.16	89.5	3.84	108.7